







**Full Specification List (RoHS Complied) Jan,2007** Page1 of 2

All Inductance, Resistance & Size of the coils can be made according to customer's requirement.

MODEL	DIAMETER (mm)	HEIGHT (mm)	LENGTH (mm)	IND. (mH)	RES. (Ohm)
CT2	(3.3-4.5) +/- 0.1	(1.75-3.2) +/- 0.1	5.5-6.5	(10uH-28mH) +/-25%	(0.03-110) +/-15%
					
T	(3.3-4.5) +/- 0.1	(2.0-3.3) +/- 0.1	5.5-6.5	(10uH-28mH) +/-25%	(0.03-110) +/-15%
					
RT	(2.8-4.8) +/- 0.1	(2.0-3.5) +/- 0.1	5.5-6.5	(10uH-28mH) +/-25%	(0.03-110) +/-15%
					
RCT	(2.8-4.8) +/- 0.1	(1.9-3.5) +/- 0.1	5.5-6.5	(10uH-28mH) +/-25%	(0.03-110) +/-15%
					
PIN	(3-6) +0.5/-0	(4.0-8.3) +0.5/-0		According to customer's requirement	
					
AT	3-6		18-30	According to customer's requirement	
					

**Full Specification List** (RoHS Complied) Jan,2007 Page2 of 2

All Inductance, Resistance & Size of the coils can be made according to customer's requirement.

MODEL	DIAMETER (mm)	HEIGHT (mm)	LENGTH (mm)	IND. (mH)	RES. (Ohm)
Spring Coil	According to customer's requirement				
